












Model	Wireless	Outdoor / Indoor	Image Sensor	Video Modulation	Minimum Illumination	Auto-iris	Lens Type	Max Video Resolution	Frames per Second	Networking	Digital Input / Output	Audio Capability	Video Compression	Multiple Streams	PoE	Value-added Features
 IP7142	-	Outdoor	1/3.3 inch WDR COMS	-	0.68 Lux @ F1.4 0 Lux @ F1.4 (IR Lens on)	-	3.3~12 mm F1.4(w), F2.9(t)	720x480	Up to 30 fps @ 720x480	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/MPEG-4)	Dual	Yes	IR illuminators Day/Night IP66
 IP7161	-	Indoor	1/3.2 inch CMOS	-	0.8 Lux @ F1.6	Yes	4.5 ~ 10 mm, F1.6 CS-mount	1600x1200	Up to 30fps @ 800x600 Up to 15 @ 1600x1200	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/MPEG-4)	Multiple	Yes	Day/Night SD/SDHC card slot Tamper detection Adjustment ring
 IZ7151	-	Indoor	1/4 inch progressive CCD	-	1.61 Lux @ F1.4 0.38 Lux @ F1.4 (without IR cut filter)	Yes	18X optical zoom 4.1 ~ 73.8 mm F1.4(w), F3.0(t)	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/MPEG-4)	Dual	Yes	Day/Night
 IP7139	802.11b/g	Indoor	1/3 inch CMOS	-	2.7 Lux @ F1.8	-	6.0 mm, F1.8 Fixed CS mount	1280x1024	Up to 30 fps @ 640x480 Up to 7.5fps @ 1280x1024	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/MPEG-4)	Dual	-	CF card slot
 IP7138	-	Indoor	1/3 inch CMOS	-	2.7 Lux @ F1.8	-	6.0 mm, F1.8 Fixed CS mount	1280x1024	Up to 30 fps @ 640x480 Up to 7.5fps @ 1280x1024	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/MPEG-4)	Dual	Yes	CF card slot
 IP7132	802.11b/g	Indoor	1/4 inch CMOS	-	0.1 Lux @ F1.6	-	4.0 mm, F1.6 Fixed CS mount	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	1 / 1	Yes	MPEG-4	-	-	-
 IP7131	-	Indoor	1/4 inch CMOS	-	0.1 Lux @ F1.6	-	4.0 mm, F1.6 Fixed CS mount	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	1 / 1	Yes	MPEG-4	-	Yes	-
 IP7134	802.11b/g	Indoor	1/4 inch CMOS	-	0.4 Lux @ F2.0	-	4.09 mm, F2.0 Fixed	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	1 / 1	Yes	Dual-Codec (MJPEG/MPEG-4)	Dual	-	-
 IP7133	-	Indoor	1/4 inch CMOS	-	0.4 Lux @ F2.0	-	4.09 mm, F2.0 Fixed	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	1 / 1	Yes	Dual-Codec (MJPEG/MPEG-4)	Dual	-	-

Model	Wireless	Outdoor / Indoor	Image Sensor	Video Modulation	Minimum Illumination	Auto-iris	Lens Type	Max Video Resolution	Frames per Second	Networking	Digital Input / Output	Audio Capability	Video Compression	Multiple Streams	PoE	Value-added Features
 IP7137	-	Indoor	1/4 inch CMOS	-	1.5 Lux @ F2.0	-	4.0 mm, F2.0 Fixed	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	-	Yes	MPEG-4	-	-	-
 IP7135	-	Indoor	1/4 inch CMOS	-	1.5 Lux @ F2.0	-	4.0 mm, F2.0 Fixed	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	-	Yes	MPEG-4	-	-	-